Flat Roof Daylighting – Climate Engineered Configuration for the UAE

Consolidated Technical Analysis

1. Strategic Context – High Solar Radiation Climate

In the UAE and Saudi Arabia:

• Intense solar radiation on horizontal roofs
• High annual cooling demand
• Energy simulation is critical during the design phase

In this environment, real performance is defined by:

• Thermal insulation (U-value)
• Effective SHGC of the complete system
• Integrated glass + solar protection configuration

Flat roof daylighting must be engineered — not selected by aesthetics alone.

2. High-Performance Configurations for Gulf Climate

Our CFU / CVU / CFP / CVP systems allow configurations specifically aligned with the most demanding energy standards in the UAE and Saudi Arabia.

Integrated Performance Comparison

Configuration	U-Value (W/m^2K)	Base SHGC	Optimized Effective SHGC	Key Performance Impact
Translucent Low Solar Gain (ISD 0110)	≈ 0.87	≈ 0.19	≈ 0.19 – 0.20	Diffused daylight with controlled solar gain.
Translucent Low Solar Gain (ISD 0110) + Programmable external solar protection with automatic operation (MSG).	≈ 0.87	≈ 0.19	≈ 0.12 – 0.15	Enhanced solar control with external shading. Significant reduction in peak heat gain.
Double Glazing + Programmable external solar protection with automatic operation (MSU).	≈ 0.75	≈ 0.52	≈ 0.23 – 0.27	Fully transparent and balanced SHGC ratio.
Triple Glazing + Programmable external solar protection with automatic operation (MSU).	≈ 0.60	≈ 0.49	≈ 0.20 – 0.25	Maximum insulation, high-performance integration within the building envelope, and fully transparent. Premium

All configurations fall within — or significantly below — the recommended SHGC range for horizontal roof applications in high solar radiation climates.

3. Integrated Technical Assessment

When correctly specified and modeled during concept stage, optimized flat roof daylighting systems allow:

• Reduction of peak cooling loads
• Improved indoor thermal stability
• Better HVAC sizing optimization
• Enhanced energy modeling outcomes
• Stronger LEED / Al Sa'fat compliance positioning
• Improved building envelope continuity
• Increased long-term asset performance

The addition of external solar protection — particularly in the translucent configuration — further enhances performance by lowering effective SHGC while preserving daylight diffusion.

In cooling-dominated climates such as the UAE, controlling solar gain is more impactful than increasing insulation alone.

Overhead daylighting becomes an active engineering component of the building system — not a passive architectural feature.

Strategic Positioning

In Gulf climate conditions:

• SHGC control defines cooling demand
• U-value defines nighttime thermal stability
• External solar control defines peak performance

Precision at concept stage determines comfort, efficiency, and asset value for decades.

— George
Founder | Shams Daylighting Solutions
Dubai, UAE
🌐 www.shamsds.ae

Climate Optimized.
Energy Aligned.
Performance Driven.